

Commercial/Industrial Rotationally Molded Brine Tanks



Commercial and industrial water softeners require a large volume of brine during each regeneration.

From a capacity of 95 gallons to 500 gallons, our Rotationally Molded Brine Tanks are built to last.

Molded out of durable, chemically resistant high density polyethylene, their ¼" seamless walls won't bulge.

Rotationally Molded Brine Tanks are strong enough to handle your toughest brine requirements. (All tanks and covers are black.)

Operating Temperature Range:
40°F - 125°F (4.4°C - 51.6°C)

Also Available:

- 24" Plastic Grids
- 30" Plastic Grids

TANK SIZE	ORDER NUMBER	DIAMETER	HEIGHT	SALT CAPACITY	VOLUME	WEIGHT
24 x 48	G22448CB1P00	24"	48"	800 lbs.	95 gal.	30 lbs.
24 x 60	G22460CB1P00	24"	60"	1000 lbs.	115 gal.	32 lbs.
30 x 48	G23048CB1P00	30"	48"	1200 lbs.	145 gal.	48 lbs.
30 x 60	G23060CB1P00	30"	60"	1600 lbs.	180 gal.	56 lbs.
39 x 48	G23948CB1P00	39"	48"	2200 lbs.	250 gal.	67 lbs.
39 x 60	G23960CB1P00	39"	60"	2700 lbs.	300 gal.	80 lbs.
42 x 60	G24260CB1P00	42"	60"	3100 lbs.	350 gal.	84 lbs.
50 x 60	G25060CB1P00	50"	60"	4500 lbs.	500 gal.	107 lbs.