

# Clack®

## WS2EE

### WATER SPECIALIST CONTROL VALVE



**NSF**

Certified to NSF/ANSI 44, 61 and 372.

- 2" Top mount control valve suited for commercial/industrial applications
- Epoxy coated lead free brass valve body\*
- Economical stainless steel optional meter assembly
- Service flow rate of 115 gpm, backwash 80 gpm
- Solid state microprocessor with easy access front panel settings
- Front panel display for time of day, days until next regeneration, volume remaining, current flow rate and total volume used (Totalizer)
- Four methods to initiate regeneration; meter immediate, meter delayed, time clock delayed or pressure differential
- Optional double backwash feature offers optimum regeneration, cleaning ability and efficiency
- Fully adjustable cycle times with 6-cycle control delivers controlled backwash, downflow brining or upflow brining, slow rinse, second backwash, fast rinse, refill and downflow service
- Coin Cell Lithium battery back-up with an 8 hour carry over
- 12-volt output AC Adapter provides safe and easy installation
- Post treated water regenerant refill
- Reliable and proven DC drive
- Patented one piece expanding seal spacer stack assembly U.S. Patent 6,402,944
- Patented linearly reciprocating piston operation U.S. Patent 6,444,127



Optional 2" Meter

# Water Specialist 2" EE Control Specifications

Inlet/Outlet (1) .....	2" Female NPT
Cycles .....	up to 6
Valve Material .....	Lead free brass
Regeneration .....	Downflow

## CONTROL VALVE FLOW RATES

Service @15 psi drop (includes meter).....	115 gpm
Backwash @ 25 psi drop .....	80 gpm
Cv Service .....	29.7
Cv Backwash .....	16.0

## OPERATING PRESSURES

Minimum/Maximum .....	20 psi – 125 psi
-----------------------	------------------

## OPERATING TEMPERATURES

Minimum/Maximum .....	40° – 110° F
-----------------------	--------------

## METER SPECIFICATIONS

Accuracy .....	± 5%
Flow Rate Range.....	1.5 – 150 gpm
Gallon Range.....	20 – 1,500,000 gallons
Totalizer .....	1 – 9,999,000 gallons

## DIMENSIONS & WEIGHT

Distributor Pilot	
Valve bodies with 2" Female NPT Inlet & Outlet .....	1.90" OD (1.5" NPS)
Drain Line Connection (drain line adapters not included) .....	1.5" Female NPT
Brine Line Adapters Included.....	1" Male NPT elbow, 3/4" x 1" solvent weld elbow and 1/2" OD Poly Tube Compression
Mounting Base.....	4" - 8 UN
Height From Top Of Tank.....	8.5"
Shipping Weight With Meter .....	29 lbs.

## ELECTRICAL SPECIFICATIONS

	<b>AC Adapter</b>	
	<u>U.S.</u>	<u>International</u>
Supply Voltage .....	120V AC.....	230V AC
Supply Frequency .....	60 Hz.....	50Hz
Output Voltage .....	20V AC.....	20V AC
Output Current .....	750 mA.....	750mA

## TANK APPLICATIONS

Water Softener .....	12" – 48" diameter
Water Filter (2).....	12" – 36" diameter

## CYCLES OF OPERATION

	<u>Softener</u>	<u>Filter</u>
Cycle	Range of time in minutes	
1. Backwash 1 <sup>st</sup> (upflow) .....	1-95.....	Backwash 1-95
2. Regenerate Draw/Slow Rinse (downflow) .....	1-180	
3. Backwash 2 <sup>nd</sup> (upflow).....	1-95	
4. Fast Rinse (downflow) .....	1-95.....	Rinse 1-95
5. Regenerant Refill (in service with treated water).....	0.1-99.0 or off	
6. Service (downflow)		

### Options: Backwash Filter, Weather Cover

Compatible with the following typical concentrations of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. See Distributor Pilot  
 2. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area