

DUPLEX NXT2 SOFTENER

MODEL NO. 29/17NXT2-DUP-120-C2441

CAPACITY: (each tank)

- MIN. 96,000 grs. @ 10 lbs./cu. ft.
- MAX. 120,000 grs. @ 15 lbs./cu. ft.

FLOW RATE: (each tank)

- NORMAL 40 gpm.
- PEAK 57 gpm.
- BACKWASH 7 gpm.

TANK SIZE: 16" x 65"

COMPOSITE

MEDIA: (each tank)

- RESIN 4 cu. ft.
- GRAVEL 75 lbs.

PIPE SIZE:

- INLET 2"
- OUTLET 2"
- DRAIN 1"
- BRINE 1/2"
- METER 2"

BRINE TANK

MODEL NO. BT2441R-454HF-5

TANK SIZE: 24" x 41"

POLYETHYLENE

CAPACITY:

- 81 gal.s.
- 700 lbs./salt

BRINE VALVE: 454HF

BRINE WELL: 5"

WEIGHT (APPROX)

TOTAL SHIPPING 850 lbs.

NOTE:
ALL DASHED PIPE, VALVES,
AND FITTINGS NOT PROVIDED
BY NELSEN CORPORATION.


SPACE REQUIRED (APPROX)

64"L x 24"W x 78"H

PEAK FLOWS ARE NOT
RECOMMENDED FOR EXTENDED
PERIODS OF TIME.

DO NOT SCALE DRAWING

THIS DRAWING IS ISSUED IN CONFIDENCE AND
CANNOT BE REPRODUCED OR USED TO
MANUFACTURE ANYTHING SHOWN OR REFERRED
TO WITHOUT DIRECT WRITTEN PERMISSION FROM
NELSEN CORPORATION.





NELSEN CORPORATION
OHIO • ARIZONA • TEXAS • FLORIDA
3250 BARBER RD - NORTON, OH 44203
800-362-9686
NELSENCORP.COM/COMMERCIAL

GENERAL ARRANGEMENT DWG.
SOFTENER 120K COMPOSITE TANK
DUPLEX NXT SYSTEM

DRAWN BY: RAR DATE: 03-03-17 CHECKED BY: PAGE 1 OF 1	DIM. NO. 29/17NXT2-DUP-120-C2441 REV:
---	---