

TRIPLEX NXT2 SOFTENER

MODEL NO. 29/17NXT2-TRI-120-C2441

CAPACITY: (each tank)

MIN. 96,000 grs. @ 10 lbs./cu.ft.

MAX. 120,000 grs. @ 15 lbs./cu.ft.

FLOW RATE: (each tank)

NORMAL 40 gpm.

PEAK 57 gpm.

BACKWASH 7 gpm.

TANK SIZE: 16" x 65"

COMPOSITE

MEDIA: (each tank)

RESIN 4 cu.ft.

GRAVEL 75 lbs.

PIPE SIZE:


INLET 2"

OUTLET 2"

DRAIN 1"

BRINE 1/2"

METER 2"



BRINE TANK

MODEL NO. BT2441R-454HF-5

TANK SIZE: 24" x 41"

POLYETHYLENE

CAPACITY: (each tank)

81 gals.

700 lbs./salt

BRINE VALVE: 454HF

BRINE WELL: 5"

NOTE:

ALL DASHED PIPE, VALVES,
AND FITTINGS NOT PROVIDED
BY NELSEN CORPORATION.

SPACE REQUIRED (APPROX)

112"L x 24"W x 78"H

PEAK FLOWS ARE NOT
RECOMMENDED FOR EXTENDED
PERIODS OF TIME.

WEIGHT (APPROX)

TOTAL SHIPPING 1,280 lbs.

DO NOT SCALE DRAWING

THIS DRAWING IS ISSUED IN CONFIDENCE AND
CANNOT BE REPRODUCED OR USED TO
MANUFACTURE ANYTHING SHOWN OR REFERRED
TO WITHOUT DIRECT WRITTEN PERMISSION FROM
NELSEN CORPORATION.

NELSEN
CORPORATION

NELSEN CORPORATION
OHIO • ARIZONA • TEXAS • FLORIDA
5151 Portside Drive, Medina, OH 44256
800-362-9686
NELSENCORP.COM/COMMERCIAL

GENERAL ARRANGEMENT DWG.
SOFTENER 120K COMPOSITE TANK
TRIPLEX NXT2 SYSTEM

DRAWN BY:	RAR
DATE:	03-06-17
CHECKED BY:	
PAGE 1 OF 1	REV:

DWG. NO.
29/17NXT2-TRI-120-C2441