

TWIN ALTERNATING SOFTENER

MODEL NO. 29/17NXT7-120-C2441

CAPACITY: (each tank)

MIN. 96,000 grs. @ 10 lbs./cu.ft.

MAX. 120,000 grs. @ 15 lbs./cu.ft.

FLOW RATE: (each tank)

NORMAL 40 gpm.

PEAK 57 gpm.

BACKWASH 7 gpm.

TANK SIZE: 16" x 65"

COMPOSITE

MEDIA: (each tank)

RESIN 4 cu.ft.

GRAVEL 75 lbs.

PIPE SIZE:

INLET 2"

OUTLET 2"

DRAIN 1"

BRINE 1/2"

METER 2"

BRINE TANK

MODEL NO. BT2441R-454HF-5

TANK SIZE: 24" x 41"

POLYETHYLENE

CAPACITY:

81 gals.

700 lbs./salt

BRINE VALVE: 454HF

BRINE WELL: 5"

WEIGHT (APPROX)

TOTAL SHIPPING 830 lbs.

NOTE:


ALL DASHED PIPE, VALVES, AND FITTINGS NOT PROVIDED BY NELSEN CORPORATION.

SPACE REQUIRED (APPROX)

64"L x 24"W x 78"H

PEAK FLOWS ARE NOT RECOMMENDED FOR EXTENDED PERIODS OF TIME.

PG-100-S



WEIGHT (APPROX)

TOTAL SHIPPING 830 lbs.

DO NOT SCALE DRAWING

THIS DRAWING IS ISSUED IN CONFIDENCE AND CANNOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING SHOWN OR REFERRED TO WITHOUT DIRECT WRITTEN PERMISSION FROM NELSEN CORPORATION.

NELSEN
CORPORATION

NELSEN CORPORATION
OHIO • ARIZONA • TEXAS • FLORIDA
5151 PORTSIDE DR. MEDINA, OHIO 44256
800-362-9686
NELSENCORP.COM/COMMERCIAL

GENERAL ARRANGEMENT DWG.
SOFTENER 120K COMPOSITE TANK
SYSTEM 7 ALTERNATING

DRAWN BY:	RAR
DATE:	03-03-17
CHECKED BY:	
PAGE 1 OF 1	REV:

DWG. NO.
29/17NXT7-120-C2441